



**Applications:** Widely used in Homes, Offices, Hotels, Restaurants, Supermarkets, Shopping Malls, etc.

MODEL	OL-DL4-15W	OL-DL4-30W
<b>Electrical Parameters</b>		
Input Voltage	AC 100-285V	AC 100-285V
Rated Power	15W	30W
Efficiency	>90%	>90%
Power Factor	>0.90	>0.90
Harmonics	<20%	<20%
<b>LED Details</b>		
Beam Angle	25°	25°
Colour Temperature (CCT)	3000K	3000K
Lumens	70 Lm/W	70 Lm/W
Luminous Flux	1050 lm	2100 lm
CRI	>80	>80
<b>Protection Parameters</b>		
Over- Current Protection	Yes	Yes
Short- Circuit Protection	Yes	Yes
Over- Voltage Protection	Yes	Yes
Dust And Water Protection	IP20	IP20
<b>Luminary Housing Details &amp; Mounting type</b>		
Mounting Type	Recessed	Recessed
Body	Aluminium	Aluminium
Heat Sink	Aluminium	Aluminium
Diffuser	Glass	Glass
<b>Certifications</b>		
BIS	Tested and Approved	Tested and Approved
ROHS	Yes	Yes
<b>Dimension</b>		
Outer Dimension	136mm x 136mm	136mm x 248mm
Cutting Dimension	125mm x 125mm	125mm x 230mm

**Light distribution**

